

# SQUARE DOWNLIGHTS

Our LED square downlight with a range from 10W - 30W has a high light intensity. This downlight is ideal for domestic or commercial lighting applications where a more architectural style product is needed. The DLQ CT downlight has a variable colour range adjustment from warm white to cool white depending on the mood required in the room. This fitting is also dimmable to give even further flexibility in lighting controlled by the G-Smart App or the hand held remote. The fitting is suitable for a range of home lighting or commercial applications.

Product Code	Voltage (V)	Wattage (W)	Power Factor	Luminous Flux (Lm)	Beam Angle	Cutout size (mm)	Colour temp	Dimmable
DLQ125CW	240V AC	10W	>0.85	930	120	125x125	6000 (CW)	Yes
DLQ125WW	240V AC	10W	>0.85	885	120	125x125	3200 (WW)	Yes
DLQ160CW	240V AC	20W	>0.85	1790	120	160x160	6000 (CW)	Yes
DLQ160WW	240V AC	20W	>0.85	1766	120	160x160	3200 (WW)	Yes
DLQ195CW	240V AC	30W	>0.85	2745	120	195x195	6000 (CW)	Yes
DLQ195WW	240V AC	30W	>0.85	2710	120	195x195	3200 (WW)	Yes

Note : Lights are available in white finish



DLQ series can be controlled with G-Smart App and control your lighting from anywhere



The hand held remote can be used for local wireless control only available for DLQ series



