

20W - 38W DOWNLIGHTS

These high output LED downlights are ideal for commercial lighting replacements that require a large cutout size combined with low power consumption making this fitting an easy replacement option. Anti glare lens, No Mercury, No UV light, No hazardous materials, excellent light stability and colour render. The DL200CT series downlight has a variable colour range adjustment from warm white to cool white depending on the mood required in the room. This fitting is also dimmable to give even further flexibility in lighting controlled by the G-Smart App or the hand held remote. The fitting is suitable for a range of commercial applications. This fitting is also dimmable to give even further flexibility in the lighting control.

Product Code	Voltage (V)	Wattage (W)	Power Factor	IP Rating	Luminous Flux (Lm)	Beam Angle	Cutout size (mm)	Colour temp	Dimmable
DL20020	240V AC	20W	>0.85	IP44	2010	120	200	3200 - 6000K	Yes
DL20028	240V AC	28W	>0.85	IP44	2860	120	200	3200 - 6000K	Yes
DL20038	240V AC	38W	>0.85	IP44	3860	120	200	3200 - 6000K	Yes
DL20020CT	240V AC	20W	>0.85	IP44	2010	120	200	3000/4000/6000K	Yes
DL20028CT	240V AC	28W	>0.85	IP44	2860	120	200	3000/4000/6000K	Yes
DL20028CT	240V AC	38W	>0.85	IP44	3680	120	200	3000/4000/6000K	Yes

Note : Lights are available in white finish only



DL200CT Series can be controlled with G-Smart App and control your lighting from anywhere

The hand held remote can be used for local wireless control only available for DL200CT Series

